

System combinations for 2 cylinders per MF-pump.

Date: 2023-01-15

Stroklength	Maximal system load	Cylinder speed		Pump type	Cylinder type	
		Max. w motor	w. crank		Leg cylind	Build in
		[mm/s]	[mm/reeve]			
150 mm	200 kg	26	8,5	MF24053	AB1150	Ax1150
212 mm				MF24075	AB1212	Ax1212
300 mm				MF24106	AB1300	Ax1300
424 mm				MF24150	AB1424	Ax1424
505 mm				MF24212	AB1505	Ax1505
600 mm				MF24212	AB1600	Ax1600
150 mm	280 kg	18	6	MF24075	AB2150	Ax2150
212 mm				MF24106	AB2212	Ax2212
300 mm				MF24150	AB2300	Ax2300
424 mm				MF24212	AB2424	Ax2424
505 mm				MF24300	AB2505	Ax2505
600 mm				MF24300	AB2600	Ax2600
150 mm	280 kg (D4/D3 400kg)	13,5	4,5	MF23106	AB2150	Ax2150
212 mm				MF23150	AB2212	Ax2212
300 mm				MF23212	AB2300	Ax2300
424 mm				MF23300	AB2424	Ax2424
505 mm				MF23424	AB2505	Ax2505
600 mm				MF23424	AB2600	Ax2600
150 mm	400 kg (D4/D4 550 kg)	9	3	MF23150	AD3150	Ax3150
212 mm				MF23212	AD3212	Ax3212
300 mm				MF23300	AD3300	Ax3300
424 mm				MF23424	AD3424	Ax3424
505 mm				MF23505	AD3505	Ax3505
150 mm	550 kg*	7,5	2,5	MF23212	AD4150	Ax4150
212 mm				MF23300	AD4212	Ax4212
300 mm				MF23424	AD4300	Ax4300
356 mm				MF23505	AD4424	Ax4424
150 mm	550 kg*	5	1,5	MF22300	AD4150	Ax4150
212 mm				MF22424	AD4212	Ax4212
252 mm				MF22505	AD4300	Ax4300

* If You need longer strokes at the higher loads, please contact us and we will help You.

NOTE!! If the system is loaded unevenly, the load on each separate cylinder has to be checked, so that the max allowed load on each separate cylinder is not exceeded. See list below.

Cylinder dimension	1	2	3	4
Max. allowed load -w. plastic tubing: per cylinder [kg]	100 kg	140 kg	200 kg	275 kg
-w. copper tubing:	125 kg	175 kg	250 kg	350 kg

The technical data given in this document can be subject to a change without any further notice.

Ergonomix AB , Sweden

Tel: +46-33 22 27 80 Fax: +46-33 22 27 99 E-mail: sales@ergonomix.se